

Magnasoft™ 238-LT Textile Enhancer

Product Description

Magnasoft 238-LT textile enhancer is a copolymer based on our (AB)_n technology with each residual cyclic siloxane (D4, D5 and D6) content less than 1000 ppm, allowing compliance with the latest EU REACH SVHC requirement.

Magnasoft 238-LT textile enhancer offers outstanding softness and slickness to fabrics and garments, with minimal contribution to yellowing, shear stability loss, and thermal migration. It is water dispersible and can be effective at very low dosage levels compared to traditional amino-silicone fluids.

Magnasoft 238-LT textile enhancer is compatible with a variety of fabrics, offering particular effectiveness with synthetic/cotton blends, polyester fleece and wool.

Key Features and Typical Benefits

- Effectiveness at 3-5 g/l in the bath, as received, offering a high level of natural softness to synthetics and their blends with nature fibers
- Delivery of properties similar to those of reactive elastomeric finishes, such as durability and resistance
- Low yellowing
- Good lubricity and hand-feel to polyester fleece
- Good stability under typical finishing conditions, including jet/overflow
- Co-applicability with crease (durable press) resist resin, their catalysts and optionally OBA's
- Self-dispersibility without the need for emulsifiers, enabling potential cost savings for formulators and mills
- Direct blending into the textile finishing bath with minimal agitation
- Ease of handling
- D4, D5 and D6 content less than 1000 ppm by each

Typical Physical Properties

Appearance	Pale yellow
Viscosity at 25 °C, cSt	5000
Specific gravity at 25 °C	1.046
Amine Content, %	0.12
Preferred Diluent	Water

Typical properties are average data and are not to be used as or to develop specifications.

Potential Applications

Magnasoft 238-LT textile enhancer is an excellent candidate to consider for use in textile finishing of all synthetics, synthetic/cotton blends, polyester fleece and wool, as well as cotton fabrics.

General Considerations for Use

Typical product usage level ranges between 3-5 g/l in the bath; higher dosage levels are not recommended and, in certain cases, may be detrimental to product performance.

While Magnasoft 238-LT textile enhancer offers outstanding dilution stability, it is best to use soft water for its dilutions. If soft water is not available, the complete bath should be tested for stability before applying it in production.

Magnasoft 238-LT Textile Enhancer

Typical processing parameters are provided as follows:

1. Pad-Dry-Cure Process

Dosage	3-5 g/l
Temperature	20-40 °C
Pick-up	65-100 %
Drying	100-130 °C for 1-2 minutes
Curing	150-180 °C for 1-3 minutes

2. Exhaustion Process

Dosage	0.3-0.5 % (o.w.f)
L:R (Liquor ratio)	1:8-1:20
pH	4-5 (adjusted with acetic acid)
Temperature	30-50 °C
Time	20-30 minutes
Drying	100-130 °C for 1-2 minutes

3. Garment Washing Process

Dosage	0.3-0.5 % (o.w.f)
Conditions	Same as exhaustion process

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Customer Service Centers

For additional information, please contact our Customer Service Team

AMERICAS	+1 800 295 2392 Toll Free* +704 805 6946 Direct Number
LATIN AMERICA	BRAZIL +55 11 4534 9650 Direct Number MEXICO +52 55 2169 7670 Direct Number *All American countries
EMEA – EUROPE, MIDDLE EAST, AFRICA & INDIA	EUROPE +390510924300 Direct Number INDIA, MIDDLE EAST & AFRICA +91 44 71212207 Direct Number* *All Middle Eastern countries, Africa, India, Pakistan, Bangladesh, Sri Lanka
ASIA PACIFIC	CHINA 800 820 0202 Toll Free +86 21 3860 4892 Direct Number JAPAN +81 3 5544 311 Direct Number KOREA +82 2 6201 4600 Direct Number SOUTH EAST ASIA, AUSTRALIA & NEW ZEALAND +60 3 9206 1543 Direct Number* *All East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region)
Visit us at www.momentive.com	

DISCLAIMER - THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBE HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.

Momentive and the Momentive logo are registered trademarks of Momentive Performance Materials Inc.

Copyright 2022 Momentive Performance Materials Inc. All rights reserved.



260 Hudson River Road
Waterford, NY 12188 USA
momentive.com