


MAGNASOFT* 310

textile softener

SPECIALTY FLUIDS - TEXTILES & LEATHER







Magnasoft 310 textile softener is a linear, amino-functional silicone polymer and an excellent candidate to consider for use as a textile softener. It contains reactive end-groups, allowing for chemical bonding with many surfaces or for molecule weight build-up, in the presence of moisture.

Magnasoft 310 textile softener can be easily emulsified to obtain stable micro emulsions that provide durable softness to virtually all types of fabrics.

Key Features and Typical Benefits

- can help impart outstanding softness to most types of fabrics
- excellent affinity to fabrics
- good stretch recovery of fabrics treated
- enhances the physical properties of fabrics
- potentially compatible with a wide range of chemicals used for textile finish
- easy to formulate

Potential Applications

textile softener for most types of fabrics

Typical Physical Properties			
Property	Value		
Appearance	Translucent, light yellow liquid		
Specific Gravity, 25°C	0.98		
Viscosity, (25°C) mPa*s {cP}	1,000 {1,000}		
Refractive Index, (n _D 25)	1.408		
Amino Content, wt%	0.9		

Typical property data values should not be used as specifications Assistance and specifications are available by contacting Momentive sales office.

MAGNASOFT* 310 textile softener

Solubility

Soluble	Toluene, Mineral sprits, Methyl ethyl ketone, Isopropanol, Dimethyl silicone fluid
Insoluble	Methyl cellosolve, Water, Liquid paraffin

Emulsification Instruction

Sample Formulation(a)

15 parts	Magnasoft 310 textile softener		
1.75 parts	TDE-5 (Polyethylene Glycol Tridecyl Ether, 5EO)		
7.5 parts	TDE-10 (Polyethylene Glycol Tridecyl Ether, 10EO)		
2.8 parts	Butyl Carbitol		
0.5 parts	Hydrochloric Acid (HCI)		
72.4 parts	Water		
0.05 parts	Biocide(b)		

a) Product formulations are included as illustrative examples only. Momentive makes no representation or warranty of any kind with respect to such formulations, including, without limitation, concerning the efficacy or safety of any product manufactured using such formulations.

Guide Procedure to Emulsify

- 1) Separately pre-mix water and hydrochloric acid to prepare an acidic solution.
- 2) Charge Magnasoft 310 textile softener, TDE-5, TDE-10 and Butyl Carbitol into a mixer. Stir at 400~500rpm for 5 minutes.
- Slowly charge ¹/₃ of the acidic water (= pre-mixed water with hydrochloric acid) and then stir at 400~500rpm for 10 minutes.
- 4) Slowly charge another $^{1}/_{3}$ of the acidic water and then stir at $400\sim500$ rpm for 5 minutes.
- 5) Slowly charge the remaining $^{1}/_{3}$ of the acid water and then stir at 400~500rpm for 5 minutes.
- 6) Continue to stir for 10minutes.
- 7) Charge the biocide (if required) and continue to stir at 300~400rpm for 5 minutes.
- 8) A clear emulsion should be obtained.

⁽b) Biocides must be used in accordance with local country regulations and manufacturer's label directions.

MAGNASOFT* 310 textile softener

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers considering the use of this product should review the latest Material Safety Data Sheet and label for product safety information, handling instructions, personal protective equipment if necessary, and any special storage conditions required. Material Safety Data Sheets are available at www.momentive.com or, upon request, from any Momentive Performance Materials representative. Use of other materials in conjunction with Momentive Performance Materials products may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Emergency Service

Momentive Performance Materials maintains an around-the-clock emergency service for its products. The American Chemistry Council (CHEMTREC) and CareChem24 International also maintain an around-the-clock emergency service for all chemical products:

Momentive Performance Materials Products	All Chemical Products		
518.233.2500	CHEMTREC: 800.424.9300		
518.233.2500	CHEMTREC: 800.424.9300		
518.233.2500	CHEMTREC: 800.424.9300		
+518.233.2500	+44.(0)208.762.8322 (UK)		
(Albanian, Czech, Danish, Dutch, English, Finnish, French,			
German, Greek, Hungarian, Italian, Lithuanian, Norwegian,			
Polish, Portuguese, Romanian, Russian, Serbo-Croatian,			
Slovak, Spanish, Swedish, Turkish, Ukrainian)			
+518.233.2500	+961.3.487.287 (Lebanon)		
+518.233.2500	+44.(0)208.762.8322 (UK)		
+518.233.2500	CHEMTREC: +1-703.527.3887 (collect)		
Radio U.S. Coast Guard, which can directly contact			
Momentive Performance Materials at 518.233.2500 or			
CHEMTREC at 800.424.9300.			
	518.233.2500 518.233.2500 518.233.2500 +518.233.2500 (Albanian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Serbo-Croatian, Slovak, Spanish, Swedish, Turkish, Ukrainian) +518.233.2500 +518.233.2500 Radio U.S. Coast Guard, which can directly contact Momentive Performance Materials at 518.233.2500 or		

DO NOT WAIT. Phone if in doubt. You will be referred to a specialist for advice.

CUSTOMER SERVICE CENTERS

North America	E cs-na.silicones@momentive.com				
	Specialty Fluids	T +1.800.523.5862	F +1.304.746.1654		
	 UA, Silanes and Specialty Coatings 	T +1.800.334.4674	F +1.304.746.1623		
	 RTVs and Elastomers 	T +1.800.332.3390	F +1.304.746.1623		
	 Consumer Sealants & Construction Sealants and Adhesives 	T +1.877.943.7325	F +1.304.746.1654		
Latin America	E cs-la.silicones@momentive.com				
	Argentina & Chile	T+54.11.4862.9544	F +54.11.4862.9544		
	Brazil	T +55.11.4534.9650	F +55.11.4534.9660		
	 Mexico & Central America 	T +52.55.2169.7670	F +52.55.2169.7699		
	 Venezuela, Ecuador, Peru, 	T +58.212.285.2149	F +58.212.285.2149		
	Colombia & Caribbean				
Europe, Middle East,	E cs-eur.silicones@momentive.com	T +00.800.4321.1000			
Africa and India		T +40.21.3111848			
Pacific	E cs-ap.silicones@momentive.com				
	China	T+1.800.820.0202 or	F +86.21.5079.3725		
		T +86.21.3860.4892			
	Japan	T +0120.975.400 or	F +81.276.31.6259		
		T +81.276.20.6182			
	 Korea 	T +82.2.6201.4600	F +82.2.6201.4601		
	 Malaysia 	T +60.3.9206.1532	F +60.3.9206.1533		
	Thailand	T +662.207.3456	F +66.2207.3488		
Worldwide Hotline		T +1.607.786.8131	F +1.607.786.8309		
		T +1.800.295.2392			



Momentive Performance Materials 22 Corporate Woods Boulevard Albany, NY 12211

*Magnasoft is a trademark of Momentive Performance Materials Inc.

Momentive is a trademark of Momentive Performance Materials Holdings LLC.

Copyright 2009-2011 Momentive Performance Materials Inc. All rights reserved.

MOM-134-128-10E-GL 04/11 Printed in U.S.A.

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC., MOMENTIVE PERFORMANCE MATERIALS USA INC., MOMENTIVE PERFORMANCE MATERIALS ASIA PACIFIC PTE. LTD., MOMENTIVE PERFORMANCE MATERIALS WORLDWIDE INC., MOMENTIVE PERFORMANCE MATERIALS GMBH, THEIR SUBSIDIARIES AND AFFILIATES DOING BUSINESS IN LOCAL JURISDICTIONS (collectively "SUPPLIERS"), ARE SOLD BY THE RESPECTIVE LEGAL ENTITY OF THE SUPPLIER SUBJECT TO SUPPLIERS' STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIERS MAKE NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (I) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (II) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SUPPLIERS' PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. AFOREMENTIONED EXCLUSIONS OR LIMITATION OF LIABILITY ARE NOT APPLICABLE TO THE EXTENT THAT THE END-USE CONDITIONS AND/OR INCORPORATION CONDITIONS. EXCEPT AS PROVIDED IN SUPPLIERS' STANDARD CONDITIONS OF SALE, SUPPLIERS AND THEIR REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Suppliers' materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Suppliers' products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Suppliers' Standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Suppliers. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Suppliers or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.