

BC ANTIFOAM 2600



Description

BC Antifoam 2600 is a highly effective silicone based antifoam emulsion which has been developed for use in industrial applications where quick knockdown of foam is required.

Product Features

1. Outstanding reliability and versatility.
2. Highly effective, enabling attainment of foam control with minimum addition of non-nutrient additives.
3. Available in easy-to-use emulsion form.

Typical Properties

These values are not intended for use in preparing specifications (see table).

Method of Use

BC Antifoam 2600 disperses easily in both hot and cold aqueous systems, requiring only mild agitation to disperse it completely in the foaming system. For maximum efficiency and economy we recommend the antifoam be diluted with water before use, in the ratio of one part of BC Antifoam 2600 to nine parts of cool soft or deionised water, the water being added slowly to the antifoam with continual low shear agitation. The quantity of antifoam required can only be found by experiment. In general between 100 and 500ppm of the product is all that is required (500ppm = 0.5 litres of product per 1000 litres of foaming media).

Applications

BC Antifoam 2600 is recommended for a wide variety of aqueous processes (for non-aqueous applications we normally recommend Antifoam C100K, including the following: Chemical manufacturing & formulations. Water & effluent treatment. BC Antifoam 2600 is effective in many processing applications where its efficiency and speed of knockdown make it a very versatile foam control agent.

In manufacturing of a wide range of chemicals and subsequent compounding and formulating, BC Antifoam 2600 offers many advantages. As well as its effectiveness, the inert nature of the product and the low levels of addition mean that there will be minimal interference in the process and subsequent applications. The product is ideally suited for use in water and effluent treatment. It is easily diluted with water making addition easy. Its non-toxic properties mean little interference with biological treatment processes

For regulatory information contact Basildon Chemicals at the address below.

Toxicity and Handling

The components of BC Antifoam 2600 have a very low order of toxicity, although prolonged contact with the skin or contact with the eyes may cause some irritation. See our Antifoam Health and Safety sheet for more information.

Storage and Shelf Life

The product should be stored below 32°C and ideally should not be allowed to freeze. Shelf life of the unopened container is 12 months from date of manufacture. If you wish to use the product after this time please contact us for approval.

Technical Service

Our technical and sales staff have considerable experience of the use of silicone products in a very wide variety of industries and the benefit of this experience is freely available to all our customers.

Basildon Chemical Co. Ltd.

(a Momentive Group Company)
Kimber Road, Abingdon, Oxon, OX14 1RZ
Telephone: 44 (1235)526677
csab@momentive.com
www.momentive.com/abingdon

Typical Properties

Percentage silicone:	20
Specific gravity (25°C):	1.0
Appearance:	Off white, viscous emulsion

Although every effort has been made to ensure that the information contained in this data sheet is reliable, we cannot be held responsible for the correctness of the information or for any loss, injury or damage which may result from its use. Also suggestions of uses should not be taken as inducements to infringe any particular patent.

December 2022