

Baysilone™ OF-OH702-4%

Baysilone* OF-OH702-4%

Description

OF OH 702-4% silicone fluid is a low molecular weight, non-solvent based, linear polydimethylsiloxane that is terminated with primary carbinol groups capable of normal alcohol reactions. The carbinol group is terminated through a non-hydrolyzable Si-C bond to the silicone polymer.

OF OH 702-4% silicone fluid may be considered for reactions with various polyurethane and polyester polymers to create a hybrid polymer.

Key Features and Benefits

- Functionalized with reactive organic groups capable of forming non-hydrolyzable covalent bonds with a variety of resin systems such as polyurethanes and polyesters.
- Strictly difunctional, and hence virtually no increase of crosslink density.
- Low molecular weight for improved compatibility in resin systems.
- Elegant and virtually permanent means of delivering silicone-like properties to resin systems.
- A hybrid polymer partially composed of OF OH 702-4% silicone fluid may exhibit improved water resistance, flexibility, slip/release, weatherability or thermal stability at both high and low temperatures.
- Virtually 100% silicone actives.

Typical Physical Properties

Property	Unit	Value
Appearance	–	Clear liquid
OH value	weight %	4
OH value 132	mg _{KOH} g ⁻¹	132
Kinetic Viscosity at 25°C	mm ² ·s ⁻¹	37
Water Solubility	–	Not soluble in water

The data values of typical physical properties should not be used as specifications that are available if contacting Momentive Performance Materials sales office.

Potential Applications

OF OH 702-4% silicone fluid contains terminal hydroxyalkyl (-CH₂-OH) groups. In contrast to the silanol (-Si-OH) terminated dimethylsiloxanes of Silopren* E or Silopren C fluid series, OF OH 702-4% silicone fluid is able to form non-hydrolyzable ether bonds. Therefore, it may be chemically bonded into resin systems that are reactive towards alcohols, like polyurethane sealants, fabric and leather coatings or synthetic leather, potentially imparting durable silicone properties without creep and migration. OF OH 702-4% silicone fluid is hygroscopic and care should be taken to exclude moisture from the containers, as water may interfere in many of the reactions in which OF OH 702-4% silicone fluid is utilized.

Patent Status

Standard copy to come

Product Safety, Handling and Storage

Standard copy to come

Limitations

Standard copy to come

Contact Information

Email

commercial.services@momentive.com

Telephone

Americas	Latin America	EMEAI- Europe, Middle East, Africa & India	ASIA PACIFIC
+1 800 295 2392 Toll free*	Brazil +55 11 4534 9650 Direct Number	Europe +390510924300 Direct number	China 800 820 0202 Toll free +86 21 3860 4892 Direct number
All American countries	Mexico +52 55 2169 7670 Direct Number	India, Middle East & Africa + 91 44 71212207 Direct number *All Middle Eastern countries, Africa, India,	Japan +81 3 5544 3111 Direct number Korea +82 2 6201 4600

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY “SUPPLIER”), ARE SOLD SUBJECT TO SUPPLIER’S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE.

EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.