

**Technical Data Sheet** 

# Silwet<sup>™</sup> 618 Super Spreader

# Description

Silwet 618 super spreader is a proprietary trisiloxane alkoxylate based super spreading wetting agent, used where spray coverage is needed but rapid uptake of agrochemicals is undesirable.

## Key Features and Typical Benefits

- Super spreader with low to no stomatal infiltration
- Promotes spray volume reduction
- Can improve spray coverage
- Nonionic
- Meets EPA 40 CFR §180.910 requirements<sup>(1)</sup>

## **Typical Physical Properties**

| Property                                    | Value     |
|---|-----------|
| Surface Tension (0.1%, mN/m) <sup>(a)</sup> | 23        |
| Cloud Point (0.1 wt%), °C                   | 49        |
| Viscosity (cSt at 25 °C)                    | 112       |
| Specific Gravity at 25 °C                   | 1.0102    |
| Flash Point(b), °C (°F)                     | 165 (330) |

Typical properties are average data and are not to be used as or to develop specifications.

# **Potential Applications and Use Rates**

| Application | Typical Use Rate |
|-------------|------------------|
| Fungicide   | 0.01 to 0.5%     |
| Herbicide   | 0.025 to 0.1%    |
| Insecticide | 0.01 to 0.05%    |

Use rates are dependent on crop, agrochemical and spray volume requirements.

1 The components meet the requirements of U.S. regulation EPA 40 CFR §180.920, and therefore are exempt from

tolerances when used as an inert ingredient in agricultural applications in accordance with the other conditions of that regulation.

(a) Surface tension by Wilhelmy Plate Method

(b) Pensky-Martens Closed Cup, ASTM Method D93

# **General Conditions for Use**

#### In Agrochemical In-Can Formulations

Silwet 618 super spreader may be used as a component in agrochemical formulations. Although organosilicone surfactants are subject to hydrolysis under acidic or basic conditions, optimum performance is achieved by buffering the formulation to pH 6.5 -7.5. Additionally, it is recommended that Silwet 618 super spreader be used at a concentration of at least 5%, based on the total formulation.

#### As a Tank-Mix Adjuvant

Silwet 618 super spreader, when used as a tank-side adjuvant may be used to improve spray coverage, improve uptake or to allow for a reduction in spray volume. It is most effective as a tank-side adjuvant when spray mixtures are within a pH range of 5-8 and used within 24 hours of preparation.

High spray volumes, coupled with high surfactant rates, are not required to achieve sufficient coverage with Silwet 618 super spreader. In fact, it has the potential to provide adequate coverage in many low volume spray applications at rates between 0.025% and 0.1%.

#### **Patent Status**

여기에 포함된 어떠한 내용도 관련 특허가 없음을 의미하거나 특허 소유자의 허가 없이 특허에서 다루는 발명을 실행하기 위한 허가, 유도 또는 권고를 구성하는 것으로 해석되 어서는 안됩니다.

# Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an aroundthe-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

## Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

#### **Contact Information**

Email commercial.services@momentive.com

## Telephone

| Americas                      | Latin America                                      | EMEAI- Europe, Middle<br>East, Africa & India                        | ASIA PACIFIC                              |
|-------------------------------|--|--|---|
| +1 800 295 2392<br>Toll free* | <b>Brazil</b><br>+55 11 4534 9650                  | Europe<br>+390510924300  | <b>China</b><br>800 820 0202              |
| +704 805 6946                 | Direct Number                                      | Direct number  | Toll free                                 |
| Direct Number                 |  |  | +86 21 3860 4892<br>Direct number         |
| *All American<br>countries    | <b>Mexico</b><br>+52 55 2169 7670<br>Direct Number | India, Middle East &<br>Africa<br>+ 91 44 71212207<br>Direct number* | Japan<br>+81 3 5544 3111<br>Direct number |

\*All Middle Eastern Korea countries, Africa, India, +82 2 6201 4600

For literature and technical assistance, visit our website at: www.momentive.com

## **DISCLAIMER:**

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR **GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED** HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE **EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS** PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. **EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE,** SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS. PRODUCTS **OR SERVICES DESCRIBED HEREIN.** Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

# \*Silwet™는 Momentive Performance Materials Inc.의 상표입니다.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.